


## Performance Parameters


1MD015-032-XX/Z2/PA

Mounted TEC Type	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V	ACR Ohm	H mm
1MD015-032-xx/Z2/PA (N=32)						
1MD015-032-025/Z2/PA	73	1.1	0.4	4.1	7.13	0.5
1MD015-032-03/Z2/PA	73	0.9	0.4		8.55	0.55



Performance data is specified at 300K, vacuum

## Dimensions



## Manufacturing options

**A. TEC Assembly Solder**

- Lead-free Solder Sn-Sb ( $T_{\text{melt}} = 230^{\circ}\text{C}$ ) - default
- Lead-free Solder Au-Sn ( $T_{\text{melt}} = 280^{\circ}\text{C}$ ) available by request

**B. TEC Ceramics**

- AlN 100% - default
- Al<sub>2</sub>O<sub>3</sub> 100%
- Mixed solution (AlN/Al<sub>2</sub>O<sub>3</sub>)

**C. Ceramics Surface Options**

- Blank ceramics
- Metallized (Au plating)

**D. Thermistor (optional)**

Can be mounted to TEC cold side. Calibration is available by request. Various thermistor solutions are available

**E. TEC Terminal Contacts**



- WB pads or WB posts
- Flip-Chip Terminal Solution

## Performance Data

1MD015-032-025/Z2/PA



27°C, Vacuum	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-025/Z2/PA	73	1.1	0.4	4.1

50°C, N <sub>2</sub>	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-025/Z2/PA	78	1.2	0.4	4.6



75°C, N <sub>2</sub>	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-025/Z2/PA	84	1.3	0.4	5.0

85°C, N <sub>2</sub>	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-025/Z2/PA	86	1.4	0.4	5.2



**Note:** TEC performance data is specified at optimal conditions,  $T_{\text{hot}}=T_{\text{amb}}$ . Please, use TECCad Software for estimations under different conditions, or contact RMT Ltd or its branches directly.


46 Warshavskoe shosse. Moscow 115230 Russia, ph: +7-499-678-2082, fax: +7-499-678-2083, web: [www.rmtltd.ru](http://www.rmtltd.ru)

Copyright 2019. RMT Ltd. The design and specifications of products can be changed by RMT Ltd without notice.


## Performance Data

1MD015-032-03/Z2/PA


27°C, Vacuum	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-03/Z2/PA	73	0.9	0.4	4.1




50°C, N <sub>2</sub>	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-03/Z2/PA	78	1.0	0.4	4.6



75°C, N <sub>2</sub>	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-03/Z2/PA	85	1.1	0.4	5.0




85°C, N <sub>2</sub>	$\Delta T_{\max}$ K	$Q_{\max}$ W	$I_{\max}$ A	$U_{\max}$ V
1MD015-032-03/Z2/PA	87	1.2	0.4	5.2



**Note:** TEC performance data is specified at optimal conditions,  $T_{\text{hot}}=T_{\text{amb}}$ . Please, use TECCad Software for estimations under different conditions, or contact RMT Ltd or its branches directly.

## Thermoelectric Cooler Overview




## Application Tips

1. Never heat TE module more than 200°C (TEC assembled at 230°C).
2. Never heat TE module more than 260°C (TEC assembled at 280°C).
3. Never use TE module without an attached heat sink at hot (bottom) side.
3. Connect TE module to DC power supply according to polarity.
4. Do not apply DC current higher than I<sub>max</sub>.

## Installation


1. **Mechanical Mounting.** TEC is placed between two heat exchangers. This construction is fixed by screws or in another mechanical way. It is suitable for large modules (with dimensions 30x30mm and larger). Miniature types require other assembling methods in most cases.
1. **Soldering.** This method is suitable for a TE module with metallized outside surfaces. RMT provides this option and also makes pre-tinning for TE modules.
2. **Glueing.** It is an up-to-date method that is used by many customers due to availability of glues with good thermoconductive properties. A glue is usually based on some epoxy compound filled with some thermoconductive material such as graphite or diamond powders, silver, SiN and others. The application of a specific type depends on application features and the type of a TE module.



## Additional Options


### TEC Polarity

TEC Polarity can be modified by request. The specified polarity in this datasheet is typical. It can be reversed in accordance to Customer application requirements.




### Terminal Wires Options

The standard solution is based on WB pads. Terminal Wires can be attached by request. Various options for terminal wires are available. (blank, insulated wires, insulated color-coded wires, flexible multicore wires and etc).




### Optimization for WB process

The solution with WB pads (no posts) is provided by default. WB posts are available by request. The dimensions of WB posts can be modified and optimized for Customers application. WB posts are made of Copper, Au plated.




### Customized Au Patterns

Customized Au patterns on thermoelectric cooler cold side are available by request. Selective Pre-tinning over pattern is also available. Please, contact RMT Ltd for additional information about customized Au patterns requirements.



### TEC Height modification

Standard TEC height can be modified without performance changes by using ceramics of different thickness. Standard thermoelectric cooler height (specified in this datasheet) can be increased in a range +0.1...+0.8 mm by request.



## Important notes

1. TEC Performance in this datasheet is specified in typical ambient condition modes (Vacuum, +27°C; Dry N2, +50°C; Dry N2, +75°C; and Dry N2, +85°C). The performance may differ under other conditions. Please, use RMT TECCad software for detailed analysis, or contact RMT specialists for additional TEC performance info.
2. TEC ACR and Umax values are sensitive to ambient temperature. These values can be different from those specified in the datasheet at other ambient conditions. ACR and Umax raise with ambient temperature increasing.
3. TEC dTmax is specified at zero heatload, while Qmax is specified at zero dT (check Fig.1 for example). TEC dTmax and Qmax values raise with ambient temperature (check Fig. 2 for example). Please, use RMT TECCad for additional info, or contact RMT specialists directly.
4. Thermoelectric coolers have the best performance in the temperature range from near room up to +80..90°C. TEC cooling performance is less at ambient temperatures below 0°C. TECs are not suitable to operate at cryogenic temperatures.
5. Driving a TEC at I<sub>max</sub> or U<sub>max</sub> doesn't mean max performance mode. The real optimal mode may depend on operating conditions, required dT level and application heatload. In fact a better performance can be reached at operating current and voltage lower than I<sub>max</sub> and U<sub>max</sub> values specified in datasheet.
6. It is strongly recommended to avoid a direct mounting of thermoelectric cooler to pure Copper, Aluminium or Nickel materials as well as a mounting of objects from these materials on TEC cold side. Any material with high CTE (Coefficient of Thermal Expansion) may affect on TEC lifetime and even damage TEC in case of improper mounting, thermal shock and/or temperature cycling. In case of above mentioned materials necessity, it is recommended to use elastic "soft" solders or glues with large modulus of elasticity (Indium-based solders or silicon-based thermoconductive glues).
7. RMT Ltd confirms that all RMT thermoelectric coolers are qualified and meet the requirements of Telcordia GR-468 Standard. The up-to-date Reliability Report is available by request. RMT Ltd warranties thermoelectric coolers lifetime no less than 250K-300K operating hours under normal application conditions.

Fig. 1 - Understanding dT<sub>max</sub> and Q<sub>max</sub>





Fig. 2 - Single-stage TEC dT<sub>max</sub> and Q<sub>max</sub> example parameters at different ambient temperatures



## Contacts

### HEAD OFFICE

46 Warshavskoe shosse. Moscow 115230 Russia

Tel: +7-499-678-20-82

Fax: +7-499-678-20-83

E-mail: [info@rmtltd.ru](mailto:info@rmtltd.ru)

### CHINA

翰銓科技香港有限公司

Hantech Technology

RM566,5/F,Hanjing Mansion,Nanshan District,Shenzhen,China

Tel:+86-0755-86215941

Fax:+86-0755-86053039

Cell: 13760105325

E-mail: [bob.han@protecltd.com](mailto:bob.han@protecltd.com)

XIAMEN ZIBO OPTOELECTRONIC CO. LTD.

Room 120, Chuanye Building Chuanye Park,

Xiamen Torch Hi-Tech Industrial Development Zone

Xiamen, China , 361006

Tel: +86-592-5654050

Fax: +86-13606026187

E-mail: [wentyliu@foxmail.com](mailto:wentyliu@foxmail.com) (Wenty Liu)

### KOREA

Sunflower Energy

1F, 665-6, Pungdeokcheon-dong, Suji-gu,

Yongin-si, Gyeonggi-do, Korea

Tel: +82 312767992

Fax: +82 312767993

Web site: <http://www.sunfl.co.kr>

## Legal Notice


All logos, images, trademarks and product names (collectively Materials) are proprietary to RMT Ltd and/ or any of its affiliates, or subsidiaries, or other respective owners that have granted RMT Ltd the permission and/ or license to use such Materials. All images are provided by RMT Ltd. and are subjects of copyright protection.

RMT Ltd, Hantech Technology, XIAMEN ZIBO OPTOELECTRONIC CO. LTD. and Sunflower Energy do not grant a copyright license (express or implied) to the Recipient, except that Recipient may reproduce the logos, images and text materials in this press-release without any alteration for non-promotional or editorial purposes only with a written note about materials owner.

## Copyright protection warning

Graphic materials and text from this datasheet may not be used commercially without a prior response in writing on company letterhead and signed by RMT Ltd authority.

Thank you for respecting the intellectual property rights protected by the International Copyright laws. All Images contain RMT hidden watermark for the immediate proof of their origin.



RMT Image



Hidden Watermark